



SQUARE-S

Lavov surface mounted downlight from the family SQUARE-S with a power of 25W and an optics 40 degrees beam angle. CCT 3000K. With a total lumen output of 2000lm and an efficacy of 100 lm/W . Made in Die cast aluminium. and finished in Black color. DALI driver.

| Item code | 86.SD03.3323.02 Indoor | | | | |
|--------------|---------------------------|--|--|--|--|
| Product type | | | | | |
| Category | Surface Downlights | | | | |
| Family | SQUARE-S | | | | |
| Pictograms | 220 v SDCM 80 3 | | | | |
| | C € On IP 50000h L80B10 | | | | |

| Product | | | |
|----------------------------|---------------|--|--|
| Real power (W) | 25 | | |
| Real luminous flux (Lm) | 2000 | | |
| Luminous efficiency (Lm/W) | 100 | | |
| Beam angle (º) | 40 | | |
| Life time (h) | 50000h L80B10 | | |
| IP | IP20 | | |
| Colour | Black | | |
| Chip Brand | Philip | | |
| Control gear included | Yes | | |
| Control gear | DALI | | |
| Average life time (h) | 30 | | |
| Colour temperature (K) | 3000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 80 | | |

| Dimensions | |
|-------------------------|----------------|
| Product dimensions (mm) | 120X120x133 mm |

| Scheme | | | |
|--------|--|--|--|
| acheme | | | |



