



Quadro down

Lavov surface downlight from the family Quadro down with a switchable power of 8/10/15W and an optics 105,5° degrees . Switchable CCT 3000/4000/6000K. With a total lumen output of 960/1200/1800lm and a luminous efficiency of 120lm/W. Color stability SDCM80.

Item code	86.SD08.1301.01
------------------	------------------------


Product type	Indoor
---------------------	---------------

Category	Surface Downlights
-----------------	---------------------------

Family	Quadro
---------------	---------------

Subfamily	Quadro down
------------------	--------------------



Pictograms	
-------------------	--



Dimensions

Product dimensions (mm)	L260xW260xH57mm
--------------------------------	------------------------

Scheme



Product

Real power (W)	8/10/15
-----------------------	----------------

Real luminous flux (Lm)	960/1200/1800
--------------------------------	----------------------

Luminous efficiency (Lm/W)	120
-----------------------------------	------------

Beam angle (°)	105,5°
-----------------------	---------------

IP	54
-----------	-----------

Colour	white
---------------	--------------

Control gear included	yes
------------------------------	------------

Control gear	On-off
---------------------	---------------

Power Factor	>0,9
---------------------	----------------

Flicker Free	yes
---------------------	------------

Colour temperature (K)	3000/4000/6000
-------------------------------	-----------------------

Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	>80
------------	---------------

IK	IK10
-----------	-------------