



### Quadro down

Lavov surface downlight from the family Quadro down with a switchable power of 8/10/15W and an optics 105,5° degrees . Switchable CCT 3000/4000/6000K. With a total lumen output of 960/1200/1800lm and a luminous efficiency of 120lm/W. Color stability SDCM80.

<b>Item code</b>	<b>86.SD08.1301.01</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Surface Downlights</b>
-----------------	---------------------------

<b>Family</b>	<b>Quadro</b>
---------------	---------------

<b>Subfamily</b>	<b>Quadro down</b>
------------------	--------------------

<b>Pictograms</b>	    
-------------------	---





50000h L80B10
------------------

### Dimensions

<b>Product dimensions (mm)</b>	<b>L260xW260xH57mm</b>
--------------------------------	------------------------

### Scheme



### Product

<b>Real power (W)</b>	<b>8/10/15</b>
-----------------------	----------------

<b>Real luminous flux (Lm)</b>	<b>960/1200/1800</b>
--------------------------------	----------------------

<b>Luminous efficiency (Lm/W)</b>	<b>120</b>
-----------------------------------	------------

<b>Beam angle (°)</b>	<b>105,5°</b>
-----------------------	---------------

<b>IP</b>	<b>54</b>
-----------	-----------

<b>Colour</b>	<b>white</b>
---------------	--------------

<b>Control gear included</b>	<b>yes</b>
------------------------------	------------

<b>Control gear</b>	<b>On-off</b>
---------------------	---------------

<b>Power Factor</b>	<b>&gt;0,9</b>
---------------------	----------------

<b>Flicker Free</b>	<b>yes</b>
---------------------	------------

<b>Colour temperature (K)</b>	<b>3000/4000/6000</b>
-------------------------------	-----------------------

<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
----------------------------------	------------------

<b>CRI</b>	<b>&gt;80</b>
------------	---------------

<b>IK</b>	<b>IK10</b>
-----------	-------------