


Quadro down


Lavov surface sownlight from the family Quadro down with a switchable power of 8/10/15W and an optics 105,5º degrees . Switchable CCT 3000/4000/6000K. With a total lumen output of 960/1200/1800lm and a luminous efficiency of 120lm/W. Color stability SDCM3. CCT 3000/4000/6000K. On-off driver. Made in PC housing and PC cover and finished in black color. IP54and IK10 degree of protection.CRI>80.

Item code	**86.SD08.1301.02**
Product type	**Indoor**
Category	**Surface mounted Fixtures**
Family	**Quadro**
Subfamily	**Quadro down**
Pictograms	

Dimensions	
Product dimensions (mm)	**L260xW260xH57mm**

Scheme





Product	
Real power (W)	**8/10/15**
Real luminous flux (Lm)	**960/1200/1800**
Luminous efficiency (Lm/W)	**120**
Beam angle (º)	**105,5º**
IP	**54**
Colour	**black**
Control gear included	**yes**
Control gear	**On-off**
Power Factor	**>0,9**
Flicker Free	**yes**
Light source	**LED**
Type of LED	**SMD**
Colour temperature (K)	**3000/4000/6000**
Colour consistency (SDCM)	**SDCM3**
CRI	**>80**
IK	**IK10**