




### Quadro down


Lavov surface downlight from the family Quadro down with a switchable power of 10/15/20W and an optics 105,5° degrees . Switchable CCT 3000/4000/6000K. With a total lumen output of 1200/1800/2400lm and a luminous efficiency of 120lm/W. Color stability SDCM80.

|                     |   |
|---------------------|---|
| <b>Item code</b>    | <b>86.SD08.2301.02</b>  |
| <b>Product type</b> | <b>Indoor</b>   |
| <b>Category</b>     | <b>Surface Downlights</b>   |
| <b>Family</b>       | <b>Quadro</b>   |
| <b>Subfamily</b>    | <b>Quadro down</b>  |
| <b>Pictograms</b>   |  |

### Dimensions

**Product dimensions (mm)** L320xW320xH57mm

### Scheme



### Product

|                                   |                       |
|-----------------------------------|-----------------------|
| <b>Real power (W)</b>             | <b>10/15/20</b>       |
| <b>Real luminous flux (Lm)</b>    | <b>1200/1800/2400</b> |
| <b>Luminous efficiency (Lm/W)</b> | <b>120</b>            |
| <b>Beam angle (°)</b>             | <b>105,5°</b>         |
| <b>IP</b>                         | <b>54</b>             |
| <b>Colour</b>                     | <b>black</b>          |
| <b>Control gear included</b>      | <b>yes</b>            |
| <b>Control gear</b>               | <b>On-off</b>         |
| <b>Power Factor</b>               | <b>&gt;0,9</b>        |
| <b>Flicker Free</b>               | <b>yes</b>            |
| <b>Colour temperature (K)</b>     | <b>3000/4000/6000</b> |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>      |
| <b>CRI</b>                        | <b>&gt;80</b>         |
| <b>IK</b>                         | <b>IK10</b>           |