



Quadro down

Lavov surface sownlight from the family Quadro down with a switchable power of 10/15/20W and an optics $105,5^{\circ}$ degrees . Switchable CCT 3000/4000/6000K. With a total lumen output of 1200/1800/2400lm and a luminous efficiency of 120lm/W. Color stability SDCM3. CCT 3000/4000/6000K. On-off driver. Made in PC housing and PC cover and finished in black color. IP54and IK10 degree of protection.CRI>80.

		Family Quadro		
		Subfamily	Quadro down	
Dimensions		Pictograms	220 v >	
Product dimensions (mm)	L320xW320xH57mm		240 V 850°	

Item code	86.SD08.2301.02		
Product type	Indoor		
Category	Surface Downlights		
Family	Quadro		
Subfamily	Quadro down		
Pictograms	□ 220 V SI CRI 80 C€		
	50000h L80B10		

	J.P	57
320		



Product	
Real power (W)	10/15/20
Real luminous flux (Lm)	1200/1800/2400
Luminous efficiency (Lm/W)	120
Beam angle (º)	105,5º
IP	54
Colour	black
Control gear included	yes
Control gear	On-off
Power Factor	>0,9
Flicker Free	yes
Colour temperature (K)	3000/4000/6000
Colour consistency (SDCM)	SDCM<3
CRI	>80
IK	IK10

Scheme