



Quadro down

Lavov surface downlight from the family Quadro down with a switchable power of 10/15/20W and an optics 105,5° degrees . Switchable CCT 3000/4000/6000K. With a total lumen output of 1200/1800/2400lm and a luminous efficiency of 120lm/W. Color stability SDCM80.

Item code	86.SD08.2303.01
------------------	------------------------

Product type	Indoor
---------------------	---------------

Category	Surface Downlights
-----------------	---------------------------

Family	Quadro
---------------	---------------

Subfamily	Quadro down
------------------	--------------------

Pictograms	    
-------------------	---




50000h L80B10

Dimensions

Product dimensions (mm)	L320xW320xH57mm
--------------------------------	------------------------

Scheme



Product

Real power (W)	10/15/20
-----------------------	-----------------

Real luminous flux (Lm)	1200/1800/2400
--------------------------------	-----------------------

Luminous efficiency (Lm/W)	120
-----------------------------------	------------

Beam angle (°)	105,5°
-----------------------	---------------

IP	54
-----------	-----------

Colour	white
---------------	--------------

Control gear included	yes
------------------------------	------------

Control gear	DALI
---------------------	-------------

Power Factor	>0,9
---------------------	----------------

Flicker Free	yes
---------------------	------------

Colour temperature (K)	3000/4000/6000
-------------------------------	-----------------------

Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	>80
------------	---------------

IK	IK10
-----------	-------------