



Quadro up&down

Lavov surface downlight from the family Quadro up&down with a switchable power of 8/10/15W and an optics 150° down, 110° up degrees. Switchable CCT 3000/4000/6000K. With a total lumen output of 960/1200/1800lm and a luminous efficiency of 120lm/W. Color stability SDCM80.

Item code	86.SD10.1303.02
------------------	------------------------

Product type	Indoor
---------------------	---------------

Category	Surface Downlights
-----------------	---------------------------

Family	Quadro
---------------	---------------

Subfamily	Quadro up&down
------------------	---------------------------

Pictograms	
-------------------	---

Product

Real power (W)	8/10/15
-----------------------	----------------

Real luminous flux (Lm)	960/1200/1800
--------------------------------	----------------------

Luminous efficiency (Lm/W)	120
-----------------------------------	------------

Beam angle (°)	150° down, 110° up
-----------------------	---------------------------

IP	54
-----------	-----------

Colour	black
---------------	--------------

Control gear included	yes
------------------------------	------------

Control gear	DALI
---------------------	-------------

Power Factor	>0,9
---------------------	----------------

Flicker Free	yes
---------------------	------------

Colour temperature (K)	3000/4000/6000
-------------------------------	-----------------------

Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	>80
------------	---------------

IK	IK10
-----------	-------------

Dimensions

Product dimensions (mm)	L300xW300xH57mm
--------------------------------	------------------------

Scheme

