



SOLARTABLET

Lavov Solar Street light luminaire from the family SOLARTABLET, with a power of 24W and a T1 type lighting distribution. With microsensor. With a total lumen output of 4100 and a luminous efficacy of 170lm/W. Made in Die cast aluminium fixture body, PC lenses, solar panel 36W, battery type LiFePO4:12,8V, 20Ah, 256Wh. IP65. CRI80 . CCT 4500K. Driver ON-OFF. Finished in grey color. With microsensor inductive Range:≤8m & ≤180degree. Working Mode:Stand by power:50% standby at first half-hour;100% standby at second half-hour;then keep 10% standby. Induction:100% brightness 120s

Item code	86.SO20.141S.03
Product type	Outdoor
Category	Solar Street Lights
Family	SOLARTABLET
Subfamily	SOLARTABLET
Pictograms	<div>CRI 80</div> <div>IP 65</div>

Product	
Real power (W)	24
Real luminous flux (Lm)	4100
Luminous efficiency (Lm/W)	170
Beam angle (°)	T1
IP	65
Colour	grey
Control gear included	yes
Control gear	ON-OFF
Light source	LED
Type of LED	112 pieces high efficiency 3030 SMD chip
Colour temperature (K)	4500K
Colour consistency (SDCM)	<5SDCM
CRI	80

Scheme

