



SOLARTABLET

Lavov Solar Street light luminaire from the family SOLARTABLET, with a power of 48W and a T2 type lighting distribution. With microsensor. With a total lumen output of 8800 and a luminous efficacy of 170lm/W. Made in Die cast aluminium fixture body, PC lenses, solar panel 36W, battery type LiFePO4:12,8V, 32Ah, 409,6Wh. IP65. CRI80 . CCT 4500K. Driver ON-OFF. Finished in grey color. With microsensor inductive Range:≤8m & ≤180degree. Working Mode:Stand by power:50% standby at first half-hour;100% standby at second half-hour;then keep 10% standby. Induction:100% brightness 120s

Scheme		1 44. 8
	7 67	E .
		58 8. 68

86.SO20.342S.03	
Outdoor	
Solar Street Lights	
SOLARTABLET	
SOLARTABLET	
CRI IP 65	

Product		
Real power (W)	48	
Real luminous flux (Lm)	8800	
Luminous efficiency (Lm/W)	170	
Beam angle (º)	T2	
IP	65	
Colour	grey	
Control gear included	yes	
Control gear	ON-OFF	
Light source	LED	
Type of LED	224 pieces high efficiency 3030 SMD chip	
Colour temperature (K)	4500K	
Colour consistency (SDCM)	<5SDCM	
CRI	80	

