



SOLARTABLET

Lavov Solar Street light luminaire from the family SOLARTABLET, with a power of 48W and a T4 type lighting distribution. With microsensor. With a total lumen output of 8800 and a luminous efficacy of 170lm/W. Made in Die cast aluminium fixture body, PC lenses, solar panel 36W, battery type LiFePO4:12,8V, 32Ah, 409,6Wh. IP65. CRI80 . CCT 4500K. Driver ON-OFF. Finished in grey color. With microsensor inductive Range:≤8m & ≤180degree. Working Mode:Stand by power:50% standby at first half-hour;100% standby at second half-hour;then keep 10% standby. Induction:100% brightness 120s

	1 44. 8
	1
	4
7 67	5
	3
	34 34 34

86.SO20.344S.03	
Outdoor	
Solar Street Lights	
SOLARTABLET	
SOLARTABLET	
CRI IP 65	

Product	
Real power (W)	48
Real luminous flux (Lm)	8800
Luminous efficiency (Lm/W)	170
Beam angle (º)	T4
IP	65
Colour	grey
Control gear included	yes
Control gear	ON-OFF
Light source	LED
Type of LED	224 pieces high efficiency
	3030 SMD chip
Colour temperature (K)	4500K
Colour consistency (SDCM)	<5SDCM
CRI	80

