



SOLARTABLET

Lavov Solar Street light luminaire from the family SOLARTABLET, with a power of 60W and a T3 type lighting distribution. With microsensor. With a total lumen output of 10500 and a luminous efficacy of 170lm/W. Made in Die cast aluminium fixture body, PC lenses, solar panel 36W, battery type LiFePO4:12,8V, 32Ah, 409,6Wh. IP65. CRI80 . CCT 4500K. Driver ON-OFF. Finished in grey color. With microsensor inductive Range: $\leq 8\text{m}$ & $\leq 180\text{degree}$. Working Mode: Stand by power: 50% standby at first half-hour; 100% standby at second half-hour; then keep 10% standby. Induction: 100% brightness 120s

| | |
|--------------|------------------------------------|
| Item code | 86.SO20.443S.03 |
| Product type | Outdoor |
| Category | Solar Street Lights |
| Family | SOLARTABLET |
| Subfamily | SOLARTABLET |
| Pictograms | <div>CRI 80</div> <div>IP 65</div> |

| | |
|----------------------------|--|
| Product | |
| Real power (W) | 60 |
| Real luminous flux (Lm) | 10500 |
| Luminous efficiency (Lm/W) | 170 |
| Beam angle (°) | T3 |
| IP | 65 |
| Colour | grey |
| Control gear included | yes |
| Control gear | ON-OFF |
| Light source | LED |
| Type of LED | 280 pieces high efficiency 3030 SMD chip |
| Colour temperature (K) | 4500K |
| Colour consistency (SDCM) | <5SDCM |
| CRI | 80 |

Scheme

