



Marketlight

Lavov Tracklight from the family Marketlight with a power of 50 (DIP to 35, 40, 45W)W and a optic distribution 30 degrees. With a total lumen output of 8000lm and an efficiency of 160lm/W. Manufactured in steel roll formed body and PMMA lenses, length 1500mm and finished in White colour. DALI DIP SWITCH driver.

| | |
|--------------|-----------------|
| Item code | 86.T011.2413.01 |
| Product type | Indoor |
| Category | Tracklights |
| Family | Marketlight |

| | | | | | |
|------------|--|--|--|--|--|
| Pictograms | | | | | |
| | | | | | |

| | |
|-----------------------------|---------------------------|
| Product | |
| Real power (W) | 50 (DIP to 35, 40, 45W) |
| Real luminous flux (Lm) | 8000 |
| Luminous efficiency (Lm/W) | 160 |
| Beam angle (°) | 30 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Electrical class insulation | Class I |
| Operating temperature | -25 to 40 |
| Colour | White |
| Chip Brand | CTLS1-1550-40SP -06WH-DT6 |
| Control gear included | YES |
| Control gear | DALI DIP SWITCH |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |

Scheme

Unit:mm

