



### Marketlight






Lavov Tracklight from the family Marketlight with a power of 50 (DIP to 35, 40, 45W)W and a optic distribution 30 degrees. With a total lumen output of 7500lm and an efficiency of 150lm/W. Manufactured in extruded aluminium body and PMMA lenses, length 1500 mm and finished in Black colour. ON-OFF DIP SWITCH driver.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.T012.2411.02</b> |
|------------------|------------------------|


|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                    |
|-----------------|--------------------|
| <b>Category</b> | <b>Tracklights</b> |
|-----------------|--------------------|

|               |                    |
|---------------|--------------------|
| <b>Family</b> | <b>Marketlight</b> |
|---------------|--------------------|

|                   |   |
|-------------------|---|
| <b>Pictograms</b> |      |
|                   |       |

### Scheme



### Product

|                       |                                |
|-----------------------|--------------------------------|
| <b>Real power (W)</b> | <b>50 (DIP to 35, 40, 45W)</b> |
|-----------------------|--------------------------------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>7500</b> |
|--------------------------------|-------------|

|                                   |            |
|-----------------------------------|------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>150</b> |
|-----------------------------------|------------|

|                       |           |
|-----------------------|-----------|
| <b>Beam angle (°)</b> | <b>30</b> |
|-----------------------|-----------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L80B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>20</b> |
|-----------|-----------|

|                                    |                |
|------------------------------------|----------------|
| <b>Electrical class insulation</b> | <b>Class I</b> |
|------------------------------------|----------------|

|                              |                  |
|------------------------------|------------------|
| <b>Operating temperature</b> | <b>-25 to 40</b> |
|------------------------------|------------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>Black</b> |
|---------------|--------------|

|                   |                              |
|-------------------|------------------------------|
| <b>Chip Brand</b> | <b>CTLS3-1550-40SP -04BK</b> |
|-------------------|------------------------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>YES</b> |
|------------------------------|------------|

|                     |                          |
|---------------------|--------------------------|
| <b>Control gear</b> | <b>ON-OFF DIP SWITCH</b> |
|---------------------|--------------------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>4000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>80</b> |
|------------|-----------|