



GAP S-Smart

Lavov tracklight from the family GAP S-Smart with a power of 10W and a optic distribution 15°. With a total lumen output of 900lm and an efficiency of 90lm/W. Manufactured in Die Cast Aluminum and finished in White colour. Dimable Casambi ready driver.

| | |
|------------------|------------------------|
| Item code | 86.T013.1319.01 |
|------------------|------------------------|


| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|--------------------|
| Category | Tracklights |
|-----------------|--------------------|


| | |
|---------------|------------|
| Family | GAP |
|---------------|------------|

| | |
|------------------|--------------------|
| Subfamily | GAP S-Smart |
|------------------|--------------------|

| | |
|-------------------|--|
| Pictograms | <div style="display: flex; flex-wrap: wrap; gap: 5px;"> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">220 240 V</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">XX°</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">CRI 90</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">CE</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">Driver INCL.</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">On Off</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">DALI</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">IP 20</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">50000h L80B10</div> </div> |
|-------------------|--|



Scheme



Product

| | |
|-----------------------|-----------|
| Real power (W) | 10 |
|-----------------------|-----------|

| | |
|--------------------------------|------------|
| Real luminous flux (Lm) | 900 |
|--------------------------------|------------|

| | |
|-----------------------------------|-----------|
| Luminous efficiency (Lm/W) | 90 |
|-----------------------------------|-----------|

| | |
|-----------------------|------------|
| Beam angle (°) | 15° |
|-----------------------|------------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L80B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|------------------------------------|-----------------|
| Electrical class insulation | Class II |
|------------------------------------|-----------------|

| | |
|------------------------------|-----------|
| Operating temperature | 15 |
|------------------------------|-----------|

| | |
|---------------|--------------|
| Colour | White |
|---------------|--------------|

| | |
|-------------------|---------------|
| Chip Brand | Philip |
|-------------------|---------------|

| | |
|------------------------------|------------|
| Control gear included | yes |
|------------------------------|------------|

| | |
|---------------------|------------------------------|
| Control gear | Dimable Casambi ready |
|---------------------|------------------------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 90 |
|------------|-----------|