



### GAP S-Smart

Lavov tracklight from the family GAP S-Smart with a power of 30W and a optic distribution 24°. With a total lumen output of 2700lm and an efficiency of 90lm/W. Manufactured in Die Cast Aluminum and finished in White colour. Dimable Casambi ready driver.

<b>Item code</b>	<b>86.T013.3329.01</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Tracklights</b>
-----------------	--------------------

<b>Family</b>	<b>GAP</b>
---------------	------------

<b>Subfamily</b>	<b>GAP S-Smart</b>
------------------	--------------------

<b>Pictograms</b>	<div style="display: flex; flex-wrap: wrap; gap: 5px;"> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">220 240 V</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">XX°</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">CRI 90</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">CE</div> <div style="border: 1px solid gray; padding: 2px; font-size: 8px;">Driver INCL.</div> </div>
-------------------	--

On	Off
----	-----

DALI
------

IP 20
----------

### Product

<b>Real power (W)</b>	<b>30</b>
-----------------------	-----------

<b>Real luminous flux (Lm)</b>	<b>2700</b>
--------------------------------	-------------

<b>Luminous efficiency (Lm/W)</b>	<b>90</b>
-----------------------------------	-----------

<b>Beam angle (°)</b>	<b>24°</b>
-----------------------	------------

<b>Life time (h)</b>	<b>50000h L80B12</b>
----------------------	----------------------

<b>IP</b>	<b>20</b>
-----------	-----------

<b>Electrical class insulation</b>	<b>Class II</b>
------------------------------------	-----------------

<b>Operating temperature</b>	<b>15</b>
------------------------------	-----------

<b>Colour</b>	<b>White</b>
---------------	--------------

<b>Chip Brand</b>	<b>Philip</b>
-------------------	---------------

<b>Control gear included</b>	<b>yes</b>
------------------------------	------------

<b>Control gear</b>	<b>Dimable Casambi ready</b>
---------------------	------------------------------

<b>Colour temperature (K)</b>	<b>3000</b>
-------------------------------	-------------

<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
----------------------------------	------------------

<b>CRI</b>	<b>90</b>
------------	-----------

### Scheme

