



### Wall washer

Lavov tracklight from the family Wall washer with a power of 28W and a wall washer optics. With a real lumen output of 2400lm and a luminous efficiency of 85.72lm/W. Made in die cast aluminum and finished in Black colour. ON-OFF driver. CCT 4000K. CRI>90.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.T020.1451.02</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                    |
|-----------------|--------------------|
| <b>Category</b> | <b>Tracklights</b> |
|-----------------|--------------------|

|               |                    |
|---------------|--------------------|
| <b>Family</b> | <b>Wall washer</b> |
|---------------|--------------------|

**Pictograms**



### Product

|                       |           |
|-----------------------|-----------|
| <b>Real power (W)</b> | <b>28</b> |
|-----------------------|-----------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>2400</b> |
|--------------------------------|-------------|

|                                   |              |
|-----------------------------------|--------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>85.72</b> |
|-----------------------------------|--------------|

|                       |                    |
|-----------------------|--------------------|
| <b>Beam angle (°)</b> | <b>wall washer</b> |
|-----------------------|--------------------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L80B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>20</b> |
|-----------|-----------|

|                                    |                |
|------------------------------------|----------------|
| <b>Electrical class insulation</b> | <b>Class I</b> |
|------------------------------------|----------------|

|                              |                |
|------------------------------|----------------|
| <b>Operating temperature</b> | <b>-20 +35</b> |
|------------------------------|----------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>Black</b> |
|---------------|--------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>YES</b> |
|------------------------------|------------|

|                     |               |
|---------------------|---------------|
| <b>Control gear</b> | <b>ON-OFF</b> |
|---------------------|---------------|

|                     |            |
|---------------------|------------|
| <b>Light source</b> | <b>LED</b> |
|---------------------|------------|

|                    |            |
|--------------------|------------|
| <b>Type of LED</b> | <b>SMD</b> |
|--------------------|------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>4000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>90</b> |
|------------|-----------|

### Dimensions

|                                |                     |
|--------------------------------|---------------------|
| <b>Product dimensions (mm)</b> | <b>210x206x41mm</b> |
|--------------------------------|---------------------|

### Scheme

