



Suspended spotlight adjustable

Lavov tracklight from the family Suspended spotlight adjustable with a power of 12W and a beam angle of 24°. With a real lumen output of 1200lm and an efficiency of 100lm/W. Made in Die cast aluminium and finished in white color. DALI Brightness Dim 0.1~100%.

| | |
|------------------|------------------------|
| Item code | 86.TL01.R323.01 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|--------------------|
| Category | Tracklights |
|-----------------|--------------------|

| | |
|---------------|-----------------------|
| Family | Magnetic Track |
|---------------|-----------------------|

| | |
|------------------|---------------------------------------|
| Subfamily | Suspended spotlight adjustable |
|------------------|---------------------------------------|

| | |
|-------------------|--|
| Pictograms | |
|-------------------|--|



| | |
|----------------|--|
| Product | |
|----------------|--|

| | |
|-----------------------|-----------|
| Real power (W) | 12 |
|-----------------------|-----------|

| | |
|--------------------------------|---------------|
| Real luminous flux (Lm) | 1200lm |
|--------------------------------|---------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 100 |
|-----------------------------------|------------|

| | |
|-----------------------|------------|
| Beam angle (°) | 24° |
|-----------------------|------------|

| | |
|---------------|--------------|
| Colour | white |
|---------------|--------------|

| | |
|-------------------|----------------|
| Chip Brand | EPISTAR |
|-------------------|----------------|

| | |
|------------------------------|------------|
| Control gear included | YES |
|------------------------------|------------|

| | |
|---------------------|---|
| Control gear | DALI Brightness Dim 0.1~100% |
|---------------------|---|

| | |
|---------------------|------------|
| Flicker Free | Yes |
|---------------------|------------|

| | |
|------------------------------|-------------------------|
| Average life time (h) | 50000hrs L80 B10 |
|------------------------------|-------------------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 90 |
|------------|-----------|

Scheme



Photometry

