



### Luxball Smart

Lavov Tracklight from the family Luxball with a power of 30W and an optic of 24 degrees with a total lumen output of 1870 lm and an efficiency of 62,3 lm/W. CCT 4000 Kelvin. Made in Die Cast Aluminum and finished in Black colour. CASAMBI ready driver. .

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.TST8.2429.02</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                    |
|-----------------|--------------------|
| <b>Category</b> | <b>Tracklights</b> |
|-----------------|--------------------|


|               |                |
|---------------|----------------|
| <b>Family</b> | <b>Luxball</b> |
|---------------|----------------|

|                  |                      |
|------------------|----------------------|
| <b>Subfamily</b> | <b>Luxball Smart</b> |
|------------------|----------------------|

|                   |   |
|-------------------|---|
| <b>Pictograms</b> |      |
|                   |      |



### Scheme



### Product

|                       |           |
|-----------------------|-----------|
| <b>Real power (W)</b> | <b>30</b> |
|-----------------------|-----------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>1870</b> |
|--------------------------------|-------------|

|                                   |              |
|-----------------------------------|--------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>62.33</b> |
|-----------------------------------|--------------|

|                       |           |
|-----------------------|-----------|
| <b>Beam angle (°)</b> | <b>24</b> |
|-----------------------|-----------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L80B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>20</b> |
|-----------|-----------|

|                                    |                |
|------------------------------------|----------------|
| <b>Electrical class insulation</b> | <b>Class I</b> |
|------------------------------------|----------------|

|                              |                |
|------------------------------|----------------|
| <b>Operating temperature</b> | <b>-20 +35</b> |
|------------------------------|----------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>Black</b> |
|---------------|--------------|

|                   |                |
|-------------------|----------------|
| <b>Chip Brand</b> | <b>Philips</b> |
|-------------------|----------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>yes</b> |
|------------------------------|------------|

|                     |                           |
|---------------------|---------------------------|
| <b>Control gear</b> | <b>DALI Casamby ready</b> |
|---------------------|---------------------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>4000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>90</b> |
|------------|-----------|