



<p>①</p>  <p>The picture is for reference only, the actual product shall prevail! Warning: Cut off the power supply before installation to prevent electric shock!</p> <table border="1" data-bbox="100 667 560 763"><tr><td>Screw</td><td></td><td>X4</td></tr><tr><td>Screw</td><td></td><td>X4</td></tr></table>	Screw		X4	Screw		X4	<p>②</p>  <p>First select the place to be installed, place the ceiling bracket in the mounting position, and mark it with a pen core</p> <p>Then drill holes for screw A of the corresponding size. If you need to hide the outlet, An AC line control needs to be reserved in the middle of the ceiling</p>	<p>③</p>  <p>Insert screw A into the hole</p>
Screw		X4						
Screw		X4						
<p>④</p>  <p>Take out 4 screws B and use a screwdriver to fix the ceiling bracket to the ceiling.</p>	<p>⑤</p>  <p>1.Connect the ceiling AC wire to the plate terminal, wiring method: (L-live wire) (N-neutral wire) (-ground wire)</p> <p>2.Hang up the anti-fall rope</p>	<p>⑥</p>  <p>Lift the frame of the lamp and align the four notches with the four installation pillars of the ceiling bracket.</p>						
<p>⑦</p>  <p>Rotate the frame of the lamp clockwise so that it locks into place with the ceiling bracket.</p>	<p>⑧</p>  <p>Make sure that the frame of the lamp is securely attached to the ceiling bracket.</p>	<p>⑨</p>  <p>After installation, turn on the power and light up the lamps.</p>						