



Up&Down S

Código artículo	86.OW15.4341.03
Tipo de producto	Outdoor
Categoría	Appliques de pared
Familia	Up&Down S

Pictograms



50  
60 Hz

220  
240 V



850°

CRI  
80

SDCM  
3



Driver  
INCL.

50000h  
L70B10

IP  
65

Dimensions

Product dimensions (mm) 100x125x280mm

Esquema

Technical drawing of the Up&Down S wall sconce showing front, side, and detail views with dimensions:

- Front view: 125mm width, 60mm height, F100 mounting hole.
- Side view: 280mm depth, 120mm mounting bracket height, 65mm mounting hole offset.
- Detail view: 30mm mounting hole, 4-Ø5\*10 mounting holes.

Producto

Potencia real (W)	2x18
Flujo luminoso real (lm)	2x1788
Eficacia luminosa (lm/W)	99.33
Ángulo de apertura	60
Life time (h)	50000h L70B10
IP	IP65
Equipo	On-Off
Power Factor	>0,9
Temperatura de color (K)	3000
Consistencia de color (SDCM)	<5SDCM
CRI	80
IK	IK08

LAVOV  
LIGHTING

info@lavovlighting.com | +852 9189 9730 | +34637055716 | lavovlighting.com