



| | |
|-------------------------|---|
| Dimensions | |
| Product dimensions (mm) | PCB 8mm x 5m trimmable 125 mm, 64 LED/m |

Esquema

360mm(14.17")

15.6mm(0.61") LED Spacing

2835(RA90)LEDs

125mm(4.92")Cutting Length

8mm (0.31") Wide

1.4mm (0.06") High

5004mm(197.00") Max Run

TIRAS ALTA EFICIENCIA

| | |
|------------------|---|
| Código artículo | 86.LS03.1200.90 |
| Tipo de producto | Indoor |
| Categoría | Tiras LED |
| Familia | TIRAS ALTA EFICIENCIA |
| Pictograms | <div>CRI 80</div> <div>Driver EXCL.</div> <div>IP 20</div> <div>50000h L70B10</div> |

| | |
|------------------------------|---------------|
| Producto | |
| Potencia real (W) | 4.8 |
| Flujo luminoso real (lm) | 696 |
| Eficacia luminosa (lm/W) | 145 |
| Ángulo de apertura | 120 |
| Life time (h) | 50000h L70B10 |
| IP | 20 |
| Temperatura de color (K) | 2700 |
| Consistencia de color (SDCM) | SDCM<3 |
| CRI | 90 |