



### 3D Neon Cutting and Connection Guide

**1 Components**

**2 Cut and preparation**

1. Cut directly in the middle distance between the two lenses;  
2. The cutting surface should be smooth and vertical;

**3 Install Endcap**

Seal the strip and end cap by glue, then fix it for 24hours

**4 Remove the silicone at back**

**6 Fix cable on PCB by soldering**

Side feed  
Bottom feed  
End feed

Seal the gap by glue after soldering

**7 Install feeder by silicone glue**

Side feed  
Bottom feed  
End feed

Seal the strip and feeder by glue, then fix it for 24hours

### Installation Guide

**1 Mounting accessories**

**2 Mounting accessories**

Drill screw hole and install mounting accessories by screw

Gently press light strip into mounting accessories

**3 Connect wire as required**

DC24V LED Driver	24V+	Red	Vcc	White LED strip
	24V-	Black	GND	

DC24V LED Driver	24V+	Gray	24V+	RGBW LED strip
	V	Red	R	
	G	Green	G	
	B	Blue	B	
	W	White	W	

White LED strip wire connection      RGBW LED strip wire connection

**4 Installation and warning**

lighting surface

TOP VIEW      Min R 10cm

SIDE VIEW      min R 30cm

Take the product by cable or pull it is not allowed

Do not bend it in sharp angle or twist it

For assembly of LED flex neon longer than 2m carefully handling with min. 2 employees is necessary. The electrical circuit could be damaged if bending radius is too small. Stainless steel core and resin can not avoid any damage by inadequate handling.