





# Instruction Manual




### PIR sensor detection coverage

**The light keeps 100% when presence is detected for 3 minute hold time, then turn off if no presence detected.**



Product Specifications		15W	25W	
Input Voltage		100-277 Vac/120-277 Vac/100-240 Vac/220-240 Vac (Subject to the input voltage on nameplate)		
Power Frequency		50 / 60 Hz		
Outlook Dimensions		Ø135×500mm (Ø5.31"×19.69")	Ø135×1000mm (Ø5.31"×39.37")	Ø135×500mm (Ø5.31"×19.69")
Net Weight		3.8±0.3kg (8.38±0.66Lbs)	5.4±0.3kg (11.9±0.66Lbs)	3.8±0.3kg (8.38±0.66Lbs)
Working Temperature	Conventional	-20°C to +45°C (-4°F to +113°F)		
	With PIR	-20°C to +40°C (-4°F to +104°F)		
	DALI	-30°C to +50°C (-22°F to +122°F)		
Storing Temperature		-40°C to +70°C (-40°F to +158°F)		






**Dimmable**




**Warning! do not wire dim cord to high voltage, or dim function will fail.**


- For type Y attachments:  
if the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

Installation Instructions

Packing List		
	Base plate template	1PC
	Screw fixing plate	1PC
	Screw M5*16	4PCS
	Screw M6	3PCS
	Nut M6	3PCS



Physical Dimensions(mm/inch)



Installation

