















**VIALIGHT**

Street Light from the family VIALIGHT with a power of 50W and a lighting distribution type T2/T3 with a real lumen output of 6500lm, and an efficiency of 130lm/W, CRI  $\geq 70$  with a DALI driver, made in Die Cast Aluminium Body, Front Tempered Glass and finished in Grey color

|              |   |
|--------------|---|
| Item code    | 86.OS01.3473.03   |
| Product type | Outdoor   |
| Category     | Street lights   |
| Family       | VIALIGHT  |
| Pictograms   |     <br>    <br>   |

**Dimensions**

Product dimensions (mm) 285\*288\*137

**Scheme****Product**

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 50                 |
| Real luminous flux (Lm)     | 6500               |
| Luminous efficiency (Lm/W)  | 130                |
| Beam angle (°)              | T2/T3              |
| Life time (h)               | 50000h L70B10      |
| IP                          | 66                 |
| Electrical class insulation | Class I            |
| Colour                      | Grey               |
| Control gear included       | Yes                |
| Control gear                | DALI               |
| Type of LED                 | Lumileds / SMD3030 |
| Colour temperature (K)      | 4000               |
| Colour consistency (SDCM)   | SDCM<5             |
| CRI                         | $\geq 70$          |
| IK                          | 09                 |