



## MICROLOUVER

Lavov recessed fixture from the family MICROLOUVER with a

power of 36W and an optics with UGR

| ltem code    | 86.R006.2473.01                        |
|--------------|--|
| Product type | Indoor                                 |
| Category     | <b>Recessed Fixtures</b>               |
| Family       | MICROLOUVER                            |
| Pictograms   | □ 220 v<br>240 v<br>850° CRI C€        |
|              | Driver<br>INCL. Off Emerg. IP<br>1h 20 |
|              | 50000h<br>L80 <b>B</b> 10              |

| Product                     |               |
|-----------------------------|---------------|
| Real power (W)              | 36            |
| Real luminous flux (Lm)     | 4320          |
| Luminous efficiency (Lm/W)  | 120           |
| Beam angle (º)              | 90            |
| Life time (h)               | 50000h L80B10 |
| IP                          | 20            |
| Electrical class insulation | Ш             |
| Colour                      | White         |
| U. G. R                     | <17           |
| Control gear included       | Yes           |
| Control gear                | DALI          |
| Colour temperature (K)      | 4000          |
| Colour consistency (SDCM)   | SDCM<3        |
| CRI                         | 80            |

## Dimensions

Product dimensions (mm) 595x595x27

## Scheme

