

**SURFACE DOWNLIGHTS - TUBULAR-S** **Item code 86.SD01.2431.02**




| **Dimensions** | |
|---|---|
| **Product dimensions (mm)** | **Ø169X139 mm** |

## Scheme




## Photometry




## TUBULAR-S

Lavov surface mounted downlight from the family TUBULAR-S with a power of 25W and an optics 50 degrees beam angle. CCT 4000K. With a total lumen output of 2050lm and an efficacy of 82lm/W . Made in Die Cast Aluminum and finished in Black color. ON-OFF driver.

| | |
|---|---|
| **Item code** | **86.SD01.2431.02** |
| **Product type** | **Indoor** |
| **Category** | **Surface Downlights** |
| **Family** | **TUBULAR-S** |
| **Pictograms** | |

| | |
|---|---|
| **Product** | |
| **Real power (W)** | **25** |
| **Real luminous flux (Lm)** | **2050** |
| **Luminous efficiency (Lm/W)** | **82** |
| **Beam angle (º)** | **50** |
| **Life time (h)** | **50000h L80B10** |
| **IP** | **IP20** |
| **Colour** | **Black** |
| **Control gear included** | **Yes** |
| **Control gear** | **ON-OFF** |
| **Average life time (h)** | **40** |
| **Colour temperature (K)** | **4000** |
| **Colour consistency (SDCM)** | **SDCM<3** |
| **CRI** | **80** |