
**SURFACE DOWNLIGHTS - TUBULAR-S** **Item code 86.SD01.3331.03**





## Dimensions

**Product dimensions (mm)** **Ø200X139 mm**


## Scheme










## Photometry



## TUBULAR-S

Lavov surface mounted downlight from the family TUBULAR-S with a power of 30W and an optics 50 degrees beam angle. CCT 3000K. With a total lumen output of 2500lm and an efficacy of 83.33lm/W . Made in Die Cast Aluminum and finished in Silver color. ON-OFF driver.

| | |
|---|---|
| **Item code** | **86.SD01.3331.03** |
| **Product type** | **Indoor** |
| **Category** | **Surface Downlights** |
| **Family** | **TUBULAR-S** |
| **Pictograms** |  |



| **Product** | |
|---|---|
| **Real power (W)** | **30** |
| **Real luminous flux (Lm)** | **2500** |
| **Luminous efficiency (Lm/W)** | **83.33** |
| **Beam angle (º)** | **50** |
| **Life time (h)** | **50000h L80B10** |
| **IP** | **IP20** |
| **Colour** | **Silver** |
| **Control gear included** | **Yes** |
| **Control gear** | **ON-OFF** |
| **Average life time (h)** | **30** |
| **Colour temperature (K)** | **3000** |
| **Colour consistency (SDCM)** | **SDCM<3** |
| **CRI** | **80** |